

BRAIDED VINYL TUBING

Submittal Information

Part No 12407-12411
Document No. SPEC12407
Date 2020-02-02
Revision 02

General Properties

Material: Polyester Reinforced PVC
Color: Clear
Reinforcement: Textile Braid
Tube: Smooth PVC
Operating Temperature
Range: 125°F (52°C) to -40°F (-40°C)
Hardness: Durometer 83+/-3 Shore A
Toxicity: Non-toxic FDA Listed Material
Characteristics: Flexible, transparent, non-toxic, odorless, pressure resistant, abrasion resistant and corrosion resistant with much longer life. Can adding symbol lines on the surface of the hose.

Applications

- Chemical transfers
- Hydraulic lines
- Food and beverage lines
- Pneumatic lines
- Coolant lines
- Vacuum lines

Features

- For use in food and beverage lines, vacuum, coolant, hydraulic, and pneumatic lines.
- FDA compliant, can be used in potable water applications.
- Good chemical and corrosion-resistance.
- Braided PVC construction.
- Can be cut to size as needed.
- Resistant to acids, alkalis, a variety of chemicals, gases, and liquids.
- Smooth, dense bore maximizes flow and reduces sediment buildup.
- Has four times the working pressure of single wall PVC.
- CA Residents: Prop 65 WARNING(S) Prop 65 WARNING(S).

Packaging

Coils, dispenser boxes, dispenser spools



Item No.	Specifications	U/M	Std. Pkg.
12407	1/4"Id x 50'	EA	1
12408	3/8"Id 5/8"Od x 50'	EA	1
12409	1/2"Id 3/4" Od x 50'	EA	1
12410	5/8"Id x 50'	EA	1
12411	3/4"Id x 50'	EA	1