



SILICONE SEALANTS

FEATURES

- √ Prevent the growth of stain-causing mold and mildew, protecting against water damage.
- √ Superior flexibility and strong adhesion, provides a flexible, durable seal for both exterior and interior projects.
- √ Will not discolor most metal finishes such as chrome, bronze, and nickel, ensuring a clean appearance.
- √ Can be used in a wide range of applications, including air conditioners, ducts, furnaces, refrigerators, gutters, windows, and doors, etc.
- √ Can be used with a caulking gun.

INSTRUCTIONS

- 1. Remove the old caulking.
- 2. Clean the surface and allow it to dry completely.
- 3. Cut the tip of the nozzle or spout to the desired size at a 45° angle.
- 4. Load the cartridge into a caulk gun and apply the sealant.
- 5. Smooth the caulk with a tool or your finger.
- 6. Use a dry cloth to wipe off any excess from the surface.
- 7. Wait for approximately 5-10 minutes and check the adhesion of the sealant.

Note: Wait at least 24 hours for the seal to dry before using your project.







Item No.	Description	QTY	U/M
15201	SILICONE SEALANT, 10.1 OZ CLEAR	12	EA
15202	SILICONE SEALANT, 10.1 OZ WHITE	12	EA
15203	SILICONE SEALANT, 10.1 OZ ALUMINUM	12	EA



SILICONE SEALANTS

RELATED PRODUCTS



Caulking Guns

No. 36119 - 36120







