

SPRAY PAINTS

Submittal Information

Part No.	42500-42504
Document No.	SPEC42500
Date	2024-02-05
Revision	01

General Properties

Composition:	Rapid Resin
Odor:	Solvent-like
Colors Available:	Diverse
Net Weight:	10 oz (Approx.283 g)
Coverage:	25 sq. ft.
Heat Resistance:	Up to 80°C
Drying Times:	Dust-free in 5-8 mins, touch-dry in 15-20 mins, fully hard in 12 hrs.

Note: Stated times are estimates; actual drying may vary with environmental factors and substrate characteristics.

Features

- Provides excellent coverage and strong adhesion, suitable for both indoor and outdoor use.
- Delivers a smooth, polishable surface with superior flow characteristics.
- Durable against scratches, shocks, and impacts.
- Weather and UV-resistant, ensuring long-lasting protection.
- Quick-drying for faster completion; drying time depends on temperature, humidity, and coat thickness.

Applications

Ideal for painting or repairing a variety of surfaces such as wood, metal, paper, glass, leather, ceramics, paintable ABS plastics, and textiles. Suitable for DIY projects, crafts, and hobby use.

Instructions

1. Remove dust, grease, and rust; ensure the surface is clean and dry.
2. Remove residues of old paintings and rust, then sand and prime if necessary. Let dry for 1 - 2 hours.
3. Shake can for 1+ min.
4. Hold can ~12 inches from the surface; spray in smooth, even horizontal and vertical strokes.
5. Test for compatibility on a small area when painting over old surfaces.

Note: Do not spray over synthetic paints!



Item No.	Colors	Net Weight	U/M	Std. Pkg.
42500	Flat Cold Zinc Galvanize	10 oz (Approx. 283 g)	EA	6
42501	Flat Black		EA	12
42502	Flat White		EA	12
42503	Black		EA	12
42504	White		EA	12