

## NYLON CABLE TIES

### Submittal Information

Part No. 41201-41249  
 Document No. SPEC41201  
 Date 2026-01-15  
 Revision 01

### General Properties

Material: High-performance Polyamide 66 (PA66)  
 Color: Natural and Black  
 Operating Temperature: -40°F to +185°F (-40°C to +85°C)  
 Key Characteristics: Flame retardant (UL 94V-2), heat resistance, UV resistance  
 Protection Rating: UL Type 21 Enclosure Rated

### Specification

Item No.	Specifications	Min. Length (inch/mm)	Width (inch/mm)	Max Bundle Diameter (inch/mm) E	Min. Tensile Strength (lbs)	Per Bag	Std. Qty	U/M
41201	4" Natural	4.00 / 102	.100 / 2.54	.86 / 21.8	18	100	1	PK
41203	5" Natural	4.72 / 120	.100 / 2.54	1.18 / 30.0	18	100	1	PK
41213	6" Black	5.91 / 150	.188 / 4.78	1.40 / 35.5	50	100	1	PK
41205	7" Natural	7.08 / 180	.188 / 4.78	1.65 / 41.9	50	100	1	PK
41215	7" Black	7.08 / 180	.188 / 4.78	1.65 / 41.9	50	100	1	PK
41207	11" Natural	11.02 / 280	.188 / 4.78	3.00 / 76.2	50	100	1	PK
41217	11" Black	11.02 / 280	.188 / 4.78	3.00 / 76.2	50	100	1	PK
41219	11" Black (Releasable)	11" Releasable	.188 / 4.78	3.00 / 76.2	50	100	1	PK
41209	14" Natural	13.78 / 350	.188 / 4.78	3.54 / 89.9	50	100	1	PK
41221	14" Black	13.78 / 350	.188 / 4.78	3.54 / 89.9	50	100	1	PK
41211	Natural Cable Tie Assortment	Assorted 4", 7", 11"				30	1	PK
41246	Natural Cable Tie Assortment	Assorted 7" & 11"				150	1	PK
41247	Black Cable Tie Assortment	Assorted 7" & 11"				150	1	PK
41248	Natural Cable Tie Assortment	Assorted 5", 8" & 11"				450	1	PK
41249	Black Cable Tie Assortment	Assorted 5", 8" & 11"				450	1	PK

### Features

- Constructed from Polyamide 66 (PA66) for high mechanical strength and long-term dimensional stability.
- UL 94V-2 flammability rating supports compliance with electrical and industrial safety requirements.
- Reinforced head design delivers high tensile performance with low insertion force.
- Smooth, rounded edges minimize abrasion and reduce risk of insulation damage.
- Stable operating performance across a wide temperature range for indoor and outdoor applications.

