

MINI SPLIT CABLE

Submittal Information

Part No.	41580-41585
Document No.	SPEC41580
Date	2026-02-12
Revision	04

General Properties

AWG: 14, 16
Construction: 4C/Bunch-Strd Bare Copper
Conductor Colors: Black, White, Red, Green
Insulation/Jacket Material: PVC/Nylon
Jacket Color: Black
Voltage Rating: 600V
Dielectric Strength: 2.0 kV/min
Temp. Range: -4°F to 194°F (-20°C to 90°C)
UL List: 1277
PVC Insulation:
 Nom. Thickness: 0.015 in
 Min. Thickness: 0.013 in
Nylon Jacket:
 Min. Thickness: 0.005 in
PVC Overall Jacket:
 Nom. Thickness: 0.045 in
 Min. Thickness: 0.036 in
Approx. O.D.: 14-4 Cable: 0.370 in/16-4 Cable: 0.320 in

Specification

Item No.	Description	Std. Qty	U/M
41580	14-4 MINI SPLIT CABLE UL THHN, 50FT	5	RL
41581	14-4 MINI SPLIT CABLE UL THHN, 250FT	1	RL
41584	16-4 MINI SPLIT CABLE UL TFFN, 50FT	1	RL
41585	16-4 MINI SPLIT CABLE UL TFFN, 250FT	1	RL

Features

- Perfect for all ductless mini-split AC and heat pump systems requiring a 4 conductor control cable.
- UL Listed, contractor-grade, with a color-coded, stranded, black exterior jacket.
- Enables custom-length cuts to suit precise installation requirements, suitable for both indoor and outdoor environments, including wet locations.
- Features water, chemical, and UV-resistant PVC insulation.
- Capable of withstanding temperatures up to 194°F.

