

YELLOW COATED GAS CONNECTORS

Submittal Information

Part No. 12453-12495
Document No. SPEC12453
Date 2026-07-06
Revision 04

General Properties

Material: 304 Stainless Steel (Annealed)
Finish: Yellow epoxy coating
Fitting: Zinc-Plated Steel S45C
Rated Pressure: 0.5 PSI
Rated Operating Temperature: -40°F to 150°F
Certificate: CSA Listed


Features

- Gas dryer and water heater connector.
- The yellow coating provides extra corrosion protection from accidental contact with common household chemicals.
- The connector is rated for use in the temperature range of -40°F to 150°F and can be used up to a pressure of 0.5 PSI.
- Configured with pipe threaded fittings for installation.
- Metal to metal seal ensures safe, leak free performance.

Applications

- **Indoor**
Range, Dryer, Water Heater, Gas Fireplace, Garage Heater, Wall Heater, Tankless Water Heater, Furnace, Space Heaters.
- **Outdoor**
Rooftop Units, Outdoor Dryer, Stationary Outdoor Grills, Gas Fire Pits.
- **Manufactured Home**
Mobile Home Gas Meter, Cross-over Gas, Connection Kits.

Note: Not designed for high-temperature use, such as gas logs, fireplace inserts, or free-standing fireplaces.



ITEM NO.	L	A (OD)	B (ID)	FITTING	FLOW CAPACITY (NG)	STD.QTY	U/M
12453	12"	1/2"	3/8"	1/2" F x 1/2" M	102,000 BTU/H	25	EA
12454	18"	1/2"	3/8"	1/2" F x 1/2" M	93,100 BTU/H	25	EA
12455	24"	1/2"	3/8"	1/2" F x 1/2" M	85,000 BTU/H	25	EA
12456	36"	1/2"	3/8"	1/2" F x 1/2" M	71,100 BTU/H	25	EA
12457	48"	1/2"	3/8"	1/2" F x 1/2" M	60,500 BTU/H	25	EA
12458	12"	5/8"	1/2"	1/2" F x 1/2" M	180,000 BTU/H	25	EA
12459	18"	5/8"	1/2"	1/2" F x 1/2" M	164,200 BTU/H	25	EA
12460	24"	5/8"	1/2"	1/2" F x 1/2" M	150,000 BTU/H	25	EA
12461	36"	5/8"	1/2"	1/2" F x 1/2" M	125,000 BTU/H	25	EA
12462	48"	5/8"	1/2"	1/2" F x 1/2" M	106,000 BTU/H	25	EA
12463	12"	5/8"	1/2"	1/2" F x 1/2" F	180,000 BTU/H	25	EA
12464	18"	5/8"	1/2"	1/2" F x 1/2" F	164,200 BTU/H	25	EA
12465	24"	5/8"	1/2"	1/2" F x 1/2" F	150,000 BTU/H	25	EA
12466	36"	5/8"	1/2"	1/2" F x 1/2" F	125,000 BTU/H	25	EA
12467	48"	5/8"	1/2"	1/2" F x 1/2" F	106,000 BTU/H	25	EA
12468	12"	5/8"	1/2"	1/2" M x 1/2" M	180,000 BTU/H	25	EA
12469	18"	5/8"	1/2"	1/2" M x 1/2" M	164,200 BTU/H	25	EA
12470	24"	5/8"	1/2"	1/2" M x 1/2" M	150,000 BTU/H	25	EA
12471	36"	5/8"	1/2"	1/2" M x 1/2" M	125,000 BTU/H	25	EA
12472	48"	5/8"	1/2"	1/2" M x 1/2" M	106,000 BTU/H	25	EA
12481	12"	5/8"	1/2"	3/4" F x 3/4" M	180,000 BTU/H	25	EA
12482	18"	5/8"	1/2"	3/4" F x 3/4" M	164,200 BTU/H	25	EA
12483	24"	5/8"	1/2"	3/4" F x 3/4" M	150,000 BTU/H	25	EA
12484	36"	5/8"	1/2"	3/4" F x 3/4" M	125,000 BTU/H	25	EA
12485	48"	5/8"	1/2"	3/4" F x 3/4" M	106,000 BTU/H	25	EA
12486	12"	5/8"	1/2"	3/4" F x 3/4" F	180,000 BTU/H	25	EA
12487	18"	5/8"	1/2"	3/4" F x 3/4" F	164,200 BTU/H	25	EA
12488	24"	5/8"	1/2"	3/4" F x 3/4" F	150,000 BTU/H	25	EA
12489	36"	5/8"	1/2"	3/4" F x 3/4" F	125,000 BTU/H	25	EA
12490	48"	5/8"	1/2"	3/4" F x 3/4" F	106,000 BTU/H	25	EA
12491	12"	5/8"	1/2"	3/4" M x 3/4" M	180,000 BTU/H	25	EA
12492	18"	5/8"	1/2"	3/4" M x 3/4" M	164,200 BTU/H	25	EA
12493	24"	5/8"	1/2"	3/4" M x 3/4" M	150,000 BTU/H	25	EA
12494	36"	5/8"	1/2"	3/4" M x 3/4" M	125,000 BTU/H	25	EA
12495	48"	5/8"	1/2"	3/4" M x 3/4" M	106,000 BTU/H	25	EA