

MINI SPLIT CABLE

Submittal Information

Part No. 41580-41585
Document No. SPEC41580
Date 2026-02-12
Revision 04

General Properties

Ratings: Type TC-ER-JP, Direct Burial, Sunlight Resistant

AWG: 14, 16

Construction: 4C/Bunch-Strd Bare Copper

Conductor Colors: Black, White, Red, Green

Insulation/Jacket Material: PVC/Nylon

Jacket Color: Black

Voltage Rating: 600V

Dielectric Strength: 2.0 kV/min

Temp. Range: -4°F to 194°F (-20°C to 90°C)

UL List: 1277

PVC Insulation: Nom. Thickness: 0.015 in

Min. Thickness: 0.013 in

Nylon Jacket: Min. Thickness: 0.005 in

PVC Overall Jacket: Nom. Thickness: 0.045 in

Min. Thickness: 0.036 in

Approx. O.D.: 14-4 Cable: 0.370 in/16-4 Cable: 0.320 in

Specification

Item No.	Description	Std.Qty	U/M
41580	14-4 MINI SPLIT CABLE UL THHN, 50FT	5	RL
41581	14-4 MINI SPLIT CABLE UL THHN, 250FT	1	RL
41584	16-4 MINI SPLIT CABLE UL TFFN, 50FT	1	RL
41585	16-4 MINI SPLIT CABLE UL TFFN, 250FT	1	RL

Features

- Perfect for all ductless mini-split AC and heat pump systems requiring a 4 conductor control cable.
- UL Listed, contractor-grade, with a color-coded, stranded, black exterior jacket.
- Enables custom-length cuts to suit precise installation requirements, suitable for both indoor and outdoor environments, including wet locations.
- Features water, chemical, and UV-resistant PVC insulation.
- Capable of withstanding temperatures up to 194°F.

