Technical Data Sheet

DAKOTA
THE DIRECT SOURCE!

DWV PIPE

Submittal Information

Part No.	12449–12450
Document No.	SPEC12449
Date	2026-10-29
Revision	01



General Properties

Material: PVC (Polyvinyl Chloride).

Application: Drain, waste, and vent (DWV) systems in residential and commercial plumbing installations.

Pipe Type: Schedule 40, Iron Pipe Size (IPS).

Service Type: Non-pressure gravity drainage and venting.

Reference Product Standard: ASTM D2665 for solid-wall PVC DWV pipe.

Specification

Item No.	Nominal Size	O.D. (in.)	Min. Wall (in.)	Std. Qty	U/M
12449	2"	2.375	0.154	200	FT
12450	3"	3.500	0.216	200	FT

Features

- Corrosion-resistant PVC construction will not rust or pit.
- Smooth interior walls support efficient drainage flow.
- Lightweight construction simplifies handling and installation.
- Compatible with Schedule 40 PVC DWV fittings.
- Solvent-cement connections provide secure pipe-to-fitting joints.

Installation Note

Use compatible PVC DWV fittings and PVC solvent cement conforming to ASTM D2564. Use primer conforming to ASTM F656 where required by applicable codes and manufacturer instructions. Follow the manufacturer's installation instructions and applicable plumbing codes.

Dakota Sourcing, LLC
601 N. 16th St.
Beresford, SD 57004
www.dakotasourcing.com
info@dakotasourcing.com