

## LIQUID LINE DRIERS

### Submittal Information

Part No 12501-12517  
 Document No. SPEC12501  
 Date 2020-12-28  
 Revision 02

### General Properties

Type: Steel

### Features

- UL listed, maximum pressure: 4.7Mpa / 680Psig.
- High filtering ability.
- Perfect protection for the system.
- Protect the system from presence of various solid pollutants.
- Solid core drier with 80% 3A molecular sieve with 20% activated alumina, suitable for systems operating at high condensation temperatures and requiring high drying capacity.



Item No.	Specifications	U/M	Std. Pkg.
12501	1/4" Flare, 3 Cubic Inch	EA	1
12502	1/4" Sweat, 3 Cubic Inch	EA	1
12503	1/4" Flare, 5 Cubic Inch	EA	1
12504	1/4" Flare, 5 Cubic Inch	EA	1
12505	3/8" Sweat, 5 Cubic Inch	EA	1
12506	3/8" Sweat, 5 Cubic Inch	EA	1
12507	1/4" Sweat, 8 Cubic Inch	EA	1
12508	3/8" Sweat, 8 Cubic Inch	EA	1
12509	1/2" Sweat, 8 Cubic Inch	EA	1
125010	3/8" Flare, 16 Cubic Inch	EA	1
125011	3/8" Sweat, 16 Cubic Inch	EA	1
125012	1/2" Sweat, 16 Cubic Inch	EA	1
125013	3/8" Flare, 30 Cubic Inch	EA	1
125014	3/8" Sweat, 30 Cubic Inch	EA	1
125015	1/2" Sweat, 30 Cubic Inch	EA	1
125016	5/8" Flare, 30 Cubic Inch	EA	1
125017	5/8" Sweat, 30 Cubic Inch	EA	1